

T4000SG AND T4000SE HOT AIR BLOWER INFORMATION SHEET - FEATURES AND BENEFITS

Made in
Canada
By a
Canadian
Company



T-4000SG SCD

- ❖ Newly designed Motor and Impeller producing 2200-3500 CFM airflow
- ❖ 400000 to 900000 BTU Burner
- ❖ Constant Output Temperature (independent of ambient air temperature)
- ❖ Remote control Capability
- ❖ Automatic control with precipitation sensors and/or Temperature sensors
- ❖ Rail Temperature Sensor
- ❖ Bluetooth Capability Interface for Maintenance and Performance Functions
- ❖ Ethernet & Wi-Fi Capable Connectivity for Remote Monitoring & Control
- ❖ **50.8cm (20") Width X 254cm (100") Length**
- ❖ Ideal for Undersized Clearance Envelopes in Yards and Plants
- ❖ 230VAC, 480VAC or 600VAC
- ❖ Only 72 Decibels. >85 can cause hearing loss for an extended period of time.

T-4000SE SCD

- ❖ 48 KW electric option with cycle mode for temperature control
- ❖ Newly designed Motor and Impeller producing 2200-3500 CFM airflow
- ❖ Dual Cycle Mode Consistent Temperature Range (independent of ambient air temperature)
- ❖ Remote control Capability
- ❖ Automatic control with precipitation sensors and/or Temperature sensors
- ❖ Rail Temperature Sensor
- ❖ Bluetooth Capability Interface for Maintenance and Performance Functions
- ❖ Ethernet & Wi-Fi Capable Connectivity for Remote Monitoring & Control
- ❖ **50.8cm (20") Width X 254cm (100") Length**
- ❖ Ideal for Undersized Clearance Envelopes in Yards and Plants
- ❖ 600VAC or DC Compatible
- ❖ Only 72 Decibels. Noise Level of 85 or higher can cause hearing loss for extended period of time.

